4	3		2	TEM DESC	RIPTION	MATERIAL
			-  -			
			-			00 series SS
			_	2 VALVE PLUG 3 SPRING		00 series SS 00 series SS
			_			
			_	4 CARRIER 5 THERMAL A		00 series SS 00 series SS
OTES: . Cv: OPEN: 1.3, CLOSED: 0.2, DESIGN: 0.6 WEIGHT: 0.5 Lbs (0.2 Kg). MAXIMUM WORKING PRESSURE: 200 PS MAXIMUM WORKING TEMPERATURE: 25 MAXIMUM WORKING TEMPERATURE: 25	SIG (14 BAR). 0°F (121°C).			2x	1/2" FNPT	
5. NSF-61 CERTIFIED FOR USE IN ALL DOMESTIC WATER SYSTEMS.			COMPONEN	T Circ	uitSolver (CS)	
This file and any associated information and specifications				1	UNIT	
• ThermOmegaTech are provided for reference and evaluation purpos and is subject to change without notice. ThermOm		ermOmegaTech	y, ThermOmegaTech. It contains confident cch proprietary information that is		6-1/2-XX	
ThermOmegaTech, Inc. 353 Ivyland Road	makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file,		ermOmegalech property. Do not disclute to or duplicate for others except as authorized by ThermOmegaTech.		1/2"- CS	
Warminster, PA 18974-2205, USA Ph: 215-798-5978			SCALE NTS	_		
	information or specifications.	.				1 of 1

В

А